

1. Specifications

Category		Unit	PHCS1 [PHCS1]
Major	Minor		
Classification	Chassis	-	Accessory
Operation range(Leaving Water)	Cooling (min. ~ max.)	°C(DB)	5~27
	Heating (min. ~ max.)	°C(DB)	15~75
	Domestic hot water (min. ~ max.)	°C(DB)	15 ~ 80*
Power supply	Case 1	V, Φ, Hz	220-240 V~ 50Hz
Current	Current (max.)	A	0.6
Recommended circuit breaker(ELCB)	-	A	10
Connecting cable	Power supply cable (H07RN-F)	mm ² × cores	0.75 x 3C
	Communication cable (H07RN-F)	mm ² × cores	0.75 x 2C
Dimensions	Net (W x H x D)	mm	420 x 490 x 141
	Shipping (W x H x D)	mm	466 x 580 x 184
Weight	Net	kg	8.2
	Shipping	kg	10.7
Exterior	Color of chassis	-	Essence White
	RAL Code of chassis	-	RAL 9003

Note

1. Due to our policy of innovation some specifications may be changed without notification.
2. Wiring cable size must comply with the applicable local and national codes. And "Electric characteristics" chapter should be considered for electrical work and design. Especially the power cable and circuit breaker should be selected in accordance with that.
3. * DHW 65~80°C Operating is available only when the booster heater is operating.